



( APC )

Male Connector

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( APCF )

Female Connector

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( APL )

Male Elbow

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( APB )

Male Tee

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( APWT )

Male Y

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( ASC )

Male Flow Control

4-M5	4-M6	4-O2 (1/8)	4-O2 (1/4)
6-M5	6-M6		
6-O1 (1/8)	6-O2 (1/4)	6-O3 (3/8)	6-O4 (1/2)
8-O1 (1/8)	8-O2 (1/4)	8-O3 (3/8)	8-O4 (1/2)
10-O1 (1/8)	10-O2 (1/4)	10-O3 (3/8)	10-O4 (1/2)
12-O1 (1/8)	12-O2 (1/4)	12-O3 (3/8)	12-O4 (1/2)
14-O3 (3/8)	14-O4 (1/2)		
16-O2 (1/4)	16-O3 (3/8)	16-O4 (1/2)	



( APE )

Equal Tee

4	6	8
10	12	14
16		



( APU )

Straight Union

4	6	8
10	12	14
16		



( APV )

Equal Elbow

4	6	8
10	12	14
16		



( APY )

Equal Y

4	6	8
10	12	14
16		



( APM )

Bulkhead Union

4	6	8
10	12	14
16		



( APZA )

Equal Cross Union

4	6	8
10	12	14
16		



( APG )

Reducer Straight Union

6-4	8-6	10-06
10-08	12-08	12-10
14-12	16-14	



( APW )

Reducer Y

6-4	8-6	10-06
10-08	12-08	12-10
14-12	16-14	



( PEG )

Reducer Tee

6-4	8-6	10-06
10-08	12-08	12-10
14-12	16-14	



( PKG )

Reducer Junction

6-4	8-6	10-06
10-08	12-08	12-10
14-12	16-14	



( APK )

Equal Junction

4	6	8
10	12	14
16		



( PEG )

Reducer Tee

6-6-8	8-8-10	8-8-12
10-10-12		

PTFE Sealing Tap

12 mm Weight  
0.1 mm Thickness  
10 Meter Length



Air Blow Gun

Technical Specification

Model	AR - TS
Size	1/4"
Pressure	Upto 12 Kg/cm <sup>2</sup>
Leakage	Bubble Tight
Media	Compressed Air



Note : Since, constant worldwide advancement in technology, We keep our rights reserved to make changes time to time in Technical Specification and Dimensions without prior notice.

